FASTROAD AR 1

SPECIFICATIES

FRAME	
MATEN	S, M, M/L, L, XL
KLEUREN	Electron Blue
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-grade composite, composite OverDrive steerer, 12x100mm thru-axle, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Giant Sport Flat, 31.8 XS:64cm, S:64cm, M:68cm, M/L: 68cm, L:68cm, XL:68cm
HANDVATTEN	Giant ErgoContact
STUURPEN	Giant Contact, 8-degree XS:70mm, S:80mm, M:90mm, M/, L:100mm, XL:110mm
ZADELPEN	Giant D-Fuse, alloy, 350mm
ZADEL	Giant ErgoContact
PEDALEN	platform pedal
AFMONTAGE	
SHIFTERS	Shimano CUES U6000, 11-speed
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano CUES
REMMEN	Tektro HD-R280, Giant MPH rotors [F]160mm, [R]160mm
REMHENDELS	Tektro HD-R280
CASSETTE	Shimano CS-LG40011, 11x45
AANDRIJVING	Shimano CN-LG500
CRANKSET	FSA Omega AGX+, 42t XS:170mm, S:170mm, M:170mm, M/L:172.5mm, L:172.5mm, XL: 175mm
BOTTOM BRACKET	threaded

WIELSET	
VELGEN	Giant S-X2 Disc wheelset
NAVEN	Giant alloy, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Maxxis Re-Fuse, tubeless, 700x40c
EXTRA'S	tubeless prepared, 42mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	42mm

Adviesprijs: € 1.399,00

GEOMETRIE

FRAME	S	M	ML	L	XL
Zitbuis Lengte (mm)	455	475	495	525	555
Zitbuis Hoek	73,5°	73,5°	73,0°	73,0°	73,0°
Frame Lengte (horizontaal) (mm)	560	575	590	610	630
Balhoofdbuis Lengte (mm)	130	155	175	200	225
Balhoofdbuis Hoek	70,5°	71,0°	71,0°	71,5°	71,5°
Vork Sprong (mm)	50	50	50	50	50
Naloop (mm)	73,7	70,4	70,4	67,1	67,1
Wielbasis (mm)	1047	1058	1069	1084	1105
Liggende achtervork lengte (mm)	435	435	435	435	435
Bottom Bracket Drop (mm)	75	75	75	75	75
Stack (mm)	552	578	597	623	646
Reach (mm)	396	404	407	419	432
Stand Over Height (mm)	736	756	773	800	826
Stuur breedte (mm)	640	680	680	680	680
Stuurpen Lengte (mm)	80	90	90	100	110
Cranklengte (mm)	170	170	172,5	172,5	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.